Hangzhou AiBai Chemical Co., Ltd

Factory add:Yipeng Xiaoshan Hangzhou Tel:86-571-22673156 Fax:86-571-83885208 Web:www.xcolorpigment.com

Material Safety Data Sheet

According to 91/155/EEC and ISO 11014-1

Printing date: 2016/01/15	Page:1/2	
1. Identification of substance and of the co	npany	
Trade Name: PIGMENT BLUE 15:6		
Hangzhou AiBai Chemical Co.,Ltd		
Room 2316, Building 17 Kaiyuan Californi	a Sunshine Plaza	
Xiaoshan Hangzhou China		
TEL: +86-571-22673158 FAX: +86-57	-83885208	
2. <u>Composition/Data on components</u>		
Substance: Pigment Blue 15:6		
CAS No: 147-14-8 EEC Symbol: None	R-Phrases: None	
3. <u>Hazards identification</u>		
No hazardous effects known	mandatany marking in accordance with the EEC	
Directive 67/584/EEC Or amendments	mandatory marking in accordance with the EEC	
4. First Aid measures		
4. <u>First Ald measures</u>		
After inhalation: Supply fresh air.		
After eye contact: Flush with plenty of pre	ssure water for 15 minutes, occasionally raising eye lids.	
After skin contact: Wash skin with mild		
5. Fire fighting measures		
Suitable extinguishing media: no restrict	on	
	its combustion products or resultant gases: none	
Special personal protection equipment:		
6. <u>Accidental release</u>		
	not sweep or wash into public stretches of water,	
sewers or sites of unknown discharge paths		
After spillage/leakage/gas/ leakage:		
Clean up immediately with wetting or abso	rbent material avoiding dusting.	
7. <u>Handling and storage</u>		
Handlen av		
Handling: Usual precautions for nuisance dust should be observed.		
Protection against fire and explosion:	be observed.	
The product is non-flammable		
Storage:		
Store in roofed places at room temperature	Keen containers tightly sealed	
Flammability Class: nor applicable.	Reep containers tightly seared.	
8. Exposure controls/personal protection		
······································		
Additional notes for design of plants equ	ipment:	
No farther details, see sec7	•	
Components with workplace-related lim	its to be monitored:	
Designation %	Type of data Unit	
Nuisance dust 100	MAK 6 mg/m3	
	TLV/TWA(USA) 10 mg/m3	
Personal protection equipment:		
Respiratory protection:		
An appropriate dust fixer has to be used if a bro	athable dust liberated.	

Material Safety Data Sheet

According to 91/155/EEC and ISO 11014-1

Printing date: 2016/01/15	Page:2/2
Trade name: PIGMENT BLUE 15:6	
9. <u>Physical and chemical properties</u>	
Appearance: blue powder	Odor: mild
Melting point:480°C	Relative density:1.61
Decomposition: None	Flammability: see 7 handling
Molecular formula:C32H16CuN8	Molecular Weight: 576.07
Tinting strength: 95-105% of the standard	Volatile matter at 105°C: 2.5%max
	Oil absorption:34-85%
Fastness to light:7-8	Fastness to heat(°C):200
Bleeding resistance water: 5	Bleeding resistance linseed oil:5
	Bleeding resistance alkalis:5
Bleeding resistance alcohol:5	Bleeding resistance xylone:5
Bleeding resistance ethyl acetate:5	
10. <u>Stability and reactivity</u>	
Hazardous decomposition products	
No decomposition at proper storage and appl	lication conditions
11. Toxicological Information	
II. <u>Itoxeological Information</u>	
Because of experience with product mention	ned, there are no recognizable hazards for human
beings, if it is correctly used and applied.	ned, there are no recognizable nazards for numar
12. Ecological information	
El Elorogical million	
Avoid filtration into waster draining or soil.	
13. Disposal considerations	
Uses should acquaint themselves with local r	regulations.
	t an approved tip or by incineration by a license
waste material processor; stack gases may ne	
14. <u>Transport information</u>	
No declaration for transport required.	
15. <u>Regulatory information</u>	
Classified according to the Directives 67/548	3/EEC, and their varions amendments, and labeled
as below:	
Warning symbols: None	
Warning words: None	
Risk Phrases: None	
Safety Phrases: None	
16. Other information	
Listed in EINECS and TSCA inventories.0	
Intended uses: Paints.	$E_{\rm T} = E_{\rm T} / 10 (USE)$
Intended uses: Paints. References: -(1)Occupational Exposure Limit	
Intended uses: Paints.	nschaft MAK-& BAT-Values.