

Hangzhou AiBai Chemical Co.,Ltd

Factory add:Yipeng Xiaoshan Hangzhou Tel:86-571-22673156 Fax:86-571-83885208 Web:www.xcolorpigment.com

Material Safety Data Sheet

According to 91/155/EEC and ISO 11014-1

Printing date: 2015/11/01

Page:1/2

1. Identification of substance and of the company

Trade Name: Pigment Red 57:1
Hangzhou AiBai Chemical Co.,Ltd
Room 2316,Building 17 Kaiyuan California Sunshine Plaza
Xiaoshan Hangzhou China
TEL: +86-571-22673158 FAX: +86-571-83885208

2. Composition/Data on components

Substance: Pigment Red 57:1
CAS No: 5281-04-9 EEC Symbol: None R-Phrases: None

3. Hazards identification

No hazardous effects known
The product is not a substance subject to mandatory marking in accordance with the EEC Directive 67/584/EEC Or amendments

4. First Aid measures

After inhalation: Supply fresh air.
After eye contact: Flush with plenty of pressure water for 15 minutes, occasionally raising eye lids.
After skin contact: Wash skin with mild soap and water.

5. Fire fighting measures

Suitable extinguishing media: no restriction
Special hazards caused by the material, its combustion products or resultant gases: none
Special personal protection equipment: none

6. Accidental release

Environmental protection conduct: Do not sweep or wash into public stretches of water, sewers or sites of unknown discharge paths.
After spillage/leakage/gas/ leakage:
Clean up immediately with wetting or absorbent material avoiding dusting.

7. Handling and storage

Handling:
Usual precautions for nuisance dust should be observed.
Protection against fire and explosion:
The product is non-flammable
Storage:
Store in roofed places at room temperature Keep containers tightly sealed.
Flammability Class: nor applicable.

8. Exposure controls/personal protection

Additional notes for design of plants equipment:

No farther details, see sec7

Components with workplace-related limits to be monitored:

Designation	%	Type of data	Unit
Nuisance dust	100	MAK	6 mg/m3
		TLV/TWA(USA)	10 mg/m3

Personal protection equipment:

Respiratory protection:

An appropriate dust fixer has to be used if a breathable dust liberated.

Material Safety Data Sheet

According to 91/155/EEC and ISO 11014-1

Printing date: 2015/11/01

Page:2/2

Trade name: Pigment Red 57:1

9. Physical and chemical properties

Appearance: Red powder
Melting point: 360°C
Decomposition: None
Molecular formula: C₁₈H₁₄N₂O₆S
Tinting strength: 95-105% of the standard
Soluble matter in water: 1.5% max
Fastness to light: 6-7
Bleeding resistance water: 3-4
Bleeding resistance acid: 1
Bleeding resistance alcohol: 5
Bleeding resistance ethyl acetate: 4

Odor: mild
Relative density: 1.42-1.80
Flammability: see 7 handling
Molecular Weight: 386.38
Volatile matter at 105°C: 2.5% max
Oil absorption: 45-55%
Fastness to heat(°C): 200
Bleeding resistance linseed oil: 1-2
Bleeding resistance alkalis: 1
Bleeding resistance xylone: 4

10. Stability and reactivity

Hazardous decomposition products
No decomposition at proper storage and application conditions

11. Toxicological Information

Because of experience with product mentioned, there are no recognizable hazards for human beings, if it is correctly used and applied.

12. Ecological information

Avoid filtration into waster draining or soil.

13. Disposal considerations

Uses should acquaint themselves with local regulations.
Disposal is usually carried out by burying at an approved tip or by incineration by a licensed waste material processor; stack gases may need to be sorubbed (see section 5 above)

14. Transport information

No declaration for transport required.

15. Regulatory information

Classified according to the Directives 67/548/EEC, and their varions amendments, and labeled as below:

Warning symbols: None
Warning words: None
Risk Phrases: None
Safety Phrases: None

16. Other information

Listed in EINECS and TSCA inventories.0
Intended uses: Paints.
References: -(1)Occupational Exposure Limits, EH/40(HSE)
 -(2)Deutsche Forschungs gerneinschaft MAK-& BAT-Values.
 -(3)A.C.D.Cowley, Polymers Paint Journal, August 7/21, 1985.