# Hangzhou AiBai Chemical Co., Ltd

Factory add: Yipeng Xiaoshan Hangzhou Tel:86-571-22673156 Fax:86-571-83885208 Web:www.xcolorpigment.com

# Material Safety Data Sheet

According to 91/155/EEC and ISO 11014-1

Printing date: 2015/09/18 Page: 1/2

# 1. Identification of substance and of the company

**Trade Name:** PIGMENT VIOLET 1 Hangzhou AiBai Chemical Co.,Ltd

Room 2316, Building 17 Kaiyuan California Sunshine Plaza

Xiaoshan Hangzhou China

TEL: +86-571-22673158 FAX: +86-571-83885208

## 2. Composition/Data on components

Substance: Pigment Violet 1

CAS No: 1326-03-0 EEC Symbol: None R-Phrases: None

#### 3. Hazards identification

No hazardous effects known

The product is not a substance subject to mandatory marking in accordance with the EEC Directive 67/584/EEC Or amendments

#### 4. First Aid measures

**After inhalation:** Supply fresh air.

**After eye contact:** Flush with plenty of pressure water for 15 minutes, occasionally raising eye lids.

**After skin contact:** Wash skin with mild soap and water.

#### 5. Fire fighting measures

Suitable extinguishing media: no restriction

Special hazards caused by the material, its combustion products or resultant gases: none Special personal protection equipment: none

6. Accidental release

**Environmental protection conduct:** Do not sweep or wash into public stretches of water, sewers or sites of unknown discharge paths.

After spillage/leakage/gas/ leakage:

Clean up immediately with wetting or absorbent material avoiding dusting.

## 7. Handling and storage

## Handling:

Usual precautions for nuisance dust should be observed.

#### Protection against fire and explosion:

The product is non-flammable

#### Storage:

Store in roofed places at room temperature Keep containers tightly sealed.

Flammability Class: nor applicable.

#### 8. Exposure controls/personal protection

# Additional notes for design of plants equipment:

No farther details, see sec7

Components with workplace-related limits to be monitored:

| <u>Designation</u> | <b>%</b> | Type of data | <u> </u> |
|--------------------|----------|--------------|----------|
| Nuisance dust      | 100      | MAK          | 6 mg/m3  |
|                    |          | TLV/TWA(USA) | 10  mg/m |

## Personal protection equipment:

#### **Respiratory protection:**

An appropriate dust fixer has to be used if a breathable dust liberated.

# Material Safety Data Sheet

## According to 91/155/EEC and ISO 11014-1

Printing date: 2015/09/18 Page:2/2

**Trade name:** PIGMENT VIOLET 1

#### 9. Physical and chemical properties

Appearance: violet powder Odor: mild

Melting point: Relative density:1.7

Decomposition: None Flammability: see 7 handling Molecular formula:C28H33N2O3+ Molecular Weight: 443.36

Tinting strength: 95-105% of the standard Volatile matter at 105°C: 2.5%max

Soluble matter in water: 1.5% max

Fastness to light:4

Oil absorption: ≤45

Fastness to heat(°C):130

Bleeding resistance water: 4
Bleeding resistance linseed oil: 3
Bleeding resistance alkalis:4-5
Bleeding resistance alkalis:4-5
Bleeding resistance xylone:5

Bleeding resistance ethyl acetate: 3

#### 10. Stability and reactivity

Hazardous decomposition products

No decomposition at proper storage and application conditions

#### 11. <u>Toxicological Information</u>

Because of experience with product mentioned, there are no recognizable hazards for human beings, if it is correctly used and applied.

## 12. Ecological information

Avoid filtration into waster draining or soil.

## 13. Disposal considerations

Uses should acquaint themselves with local regulations.

Disposal is usually carried out by burying at an approved tip or by incineration by a licensed waste material processor; stack gases may need to be sorubbed (see section 5 above)

#### 14. Transport information

No declaration for transport required.

## 15. Regulatory information

Classified according to the Directives 67/548/EEC, and their varions amendments, and labeled

as below:

Warning symbols: None Warning words: None Risk Phrases: None Safety Phrases: None

# 16. Other information

Listed in EINECS and TSCA inventories.0

Intended uses: Paints.

References: -(1)Occupational Exposure Limits, EH/40(HSE)

-(2)Deutsche Forschungs gerneinschaft MAK-& BAT-Values. -(3)A.C.D.Cowley, Polymers Paint Journal, August 7/21, 1985.