

# Hangzhou Xcolor Imp/Exp Co., Ltd

Add: Yipeng Xiaoshan Hangzhou Tel: 86-571-83885088 Fax: 86-571-83885208 Web: www.xcolor.net

## Material Safety Data Sheet

According to 91/155/EEC and ISO 11014-1

Printing date: 2016/02/15

Page: 1/2

<b>1. Identification of substance and of the company</b>  <b>Trade Name:</b> Pigment Yellow 183 Hangzhou AiBai Chemical Co., Ltd Room 2316, Building 17 Kaiyuan California Sunshine Plaza Xiaoshan Hangzhou China TEL: +86-571-22673158 FAX: +86-571-83885208												
<b>2. Composition/Data on components</b>  Substance: Pigment Yellow 183 CAS No: 65212-77-3 EEC Symbol: None R-Phrases: None												
<b>3. Hazards identification</b>  No hazardous effects known The product is not a substance subject to mandatory marking in accordance with the EEC Directive 67/584/EEC Or amendments												
<b>4. First Aid measures</b>  <b>After inhalation:</b> Supply fresh air. <b>After eye contact:</b> Flush with plenty of pressure water for 15 minutes, occasionally raising eye lids. <b>After skin contact:</b> Wash skin with mild soap and water.												
<b>5. Fire fighting measures</b>  <b>Suitable extinguishing media:</b> no restriction <b>Special hazards caused by the material, its combustion products or resultant gases:</b> none <b>Special personal protection equipment:</b> none												
<b>6. Accidental release</b>  <b>Environmental protection conduct:</b> Do not sweep or wash into public stretches of water, sewers or sites of unknown discharge paths. <b>After spillage/leakage/gas/ leakage:</b> Clean up immediately with wetting or absorbent material avoiding dusting.												
<b>7. Handling and storage</b>  <b>Handling:</b> Usual precautions for nuisance dust should be observed. <b>Protection against fire and explosion:</b> The product is non-flammable <b>Storage:</b> Store in roofed places at room temperature Keep containers tightly sealed. <b>Flammability Class:</b> nor applicable.												
<b>8. Exposure controls/personal protection</b>  <b>Additional notes for design of plants equipment:</b> No farther details, see sec7 <b>Components with workplace-related limits to be monitored:</b> <table border="1"><thead><tr><th>Designation</th><th>%</th><th>Type of data</th><th>Unit</th></tr></thead><tbody><tr><td>Nuisance dust</td><td>100</td><td>MAK</td><td>6 mg/m<sup>3</sup></td></tr><tr><td></td><td></td><td>TLV/TWA(USA)</td><td>10 mg/m<sup>3</sup></td></tr></tbody></table> <b>Personal protection equipment:</b> <b>Respiratory protection:</b> An appropriate dust fixer has to be used if a breathable dust liberated.	Designation	%	Type of data	Unit	Nuisance dust	100	MAK	6 mg/m <sup>3</sup>			TLV/TWA(USA)	10 mg/m <sup>3</sup>
Designation	%	Type of data	Unit									
Nuisance dust	100	MAK	6 mg/m <sup>3</sup>									
		TLV/TWA(USA)	10 mg/m <sup>3</sup>									

# Material Safety Data Sheet

According to 91/155/EEC and ISO 11014-1

Printing date: 2016/02/15

Page:2/2

<b>Trade name:</b> Pigment Yellow 183	
<b>9. <u>Physical and chemical properties</u></b>	
Appearance: Yellow powder	Odor: mild
Melting point: °C	Relative density: 1.46-1.6
Decomposition: None	Flammability: see 6 handling
Molecular formula: C <sub>17</sub> H <sub>15</sub> ClN <sub>4</sub> O <sub>7</sub> S <sub>2</sub>	Molecular Weight: 486.91
Tinting strength: 95-105% of the standard	Volatile matter at 105°C: 2.5% max
Soluble matter in water: 1.5% max	Oil absorption: ≤55%
Fastness to light: 5-6	Fastness to heat(°C): 200
Bleeding resistance water: 4	Bleeding resistance linseed oil: 5
Bleeding resistance acid: 5	Bleeding resistance alkalis: 5
Bleeding resistance alcohol: 5	Bleeding resistance xylone: 4
Bleeding resistance ethyl acetate: 4	
<b>10. <u>Stability and reactivity</u></b>	
Hazardous decomposition products	
No decomposition at proper storage and application conditions	
<b>11. <u>Toxicological Information</u></b>	
Because of experience with product mentioned, there are no recognizable hazards for human beings, if it is correctly used and applied.	
<b>12. <u>Ecological information</u></b>	
Avoid filtration into waster draining or soil.	
<b>13. <u>Disposal considerations</u></b>	
Uses should acquaint themselves with local regulations.	
Disposal is usually carried out by burying at an approved tip or by incineration by a licensed waste material processor; stack gases may need to be sorubbed (see section 5 above)	
<b>14. <u>Transport information</u></b>	
No declaration for transport required.	
<b>15. <u>Regulatory information</u></b>	
Classified according to the Directives 67/548/EEC, and their varions amendments, and labeled as below:	
Warning symbols:	None
Warning words:	None
Risk Phrases:	None
Safety Phrases:	None
<b>16. <u>Other information</u></b>	
Listed in EINECS and TSCA inventories.0	
Intended uses: Paints.	
References: -(1)Occupational Exposure Limits, EH/40(HSE)	
-(2)Deutsche Forschungs gemeinschaft MAK-& BAT-Values.	
-(3)A.C.D.Cowley, Polymers Paint Journal, August 7/21, 1985.	